



◆ SPECIFICATION

Model	NVRK1636P
<b>System</b>	
Main Processor	ARM Cortex A7 Processor
Operating System	Embedded LINUX
<b>Video</b>	
Input	25CH (4096×2160, 2592×1944, 2048×1536, 1920×1080, 1280×960, 1280×720, etc)
Output	1 VGA, 1 HD
<b>Audio</b>	
Input	1 Port RCA
Output	1 Port RCA(Linear, 1kΩ)
Audio Bit Rate	64kbps
Audio Compression standard	G711u, G711a, ADPCM_DVI4
<b>Alarm</b>	
Sensor Input	NO
Output	NO
Motion Detection	25 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output
<b>Display</b>	
HD Output1	Resolution:4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
HD Output2	/
VGA	Resolution:1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Display Split	25CHxD1/16CHxD1/9CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP/1CHx4k
Digital Zoom	YES
OSD	Camera Title, Time, Recording, Motion Detection
<b>Recording</b>	
Video Compression	H265/H264/H265+/H264+
Resolution	4k(4096×2160),5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536), 1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480)
Record Rate	PAL :4k@12×25fp,5MP@20×25fp,4MP@25×25fp,3MP@25×25fp,1080P@25×25fp, 960P@25×25fp,720P@25×25fp, D1@25×25fp
Record Mode	Manual\Timer\Motion Detection
<b>Playback &amp; Backup</b>	

Local Sync Playback	1CH 4K@30fps, 1CH 5MP@30fps,2CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps
Decode Capability	1CH 4K(3840×2160)@30fps
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Full Screen, Digital Zoom
Backup Mode	USB Device/Network
<b>Network</b>	
Interface	16 x RJ45 (10M/100M Adaptive Ethernet Interface)+1xRJ45 10M/100M/1000M Adaptive Ethernet Interface
Incoming Bandwidth	120MB
Outgoing Bandwidth	/
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
Onvif Version	Support Onvif 2.4
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10/MAC OS
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
POE	16 x Independent 100Mbps POE Network Interfaces(Output PowerAT mode 30W, AF mode 15W per Interface), 12/36 line order, Total Power Output $\geq$ 200W, Support Plug and Play
WIFI	/
<b>Storage</b>	
Interface Type	4 SATA Hard Disk Interface (3.5" SATA)
Capacity	Up to 24TB capacity
eSATA	/
<b>General</b>	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
USB Interface	2 USB 2.0 Interfaces
RS485	/
Power Supply	AC 100-240V
Working Environment	-10~55°C/10~90%
Dimension(WxD×H)	440*356*72(mm)
Weight	7.5KG (without HDD)

**Cantonk (guangzhou) Corporation Limited**

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA  
Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)