



◆ SPECIFICATION

Model		PT6AH18XIHHL200
Camera		
Image Sensor	1/2.8" SONY Low Illumination CMOS Sensor	
Horizontal Resolution	2MP	
Compression	H.264/H.264+/H.265/MJPEG	
S/N Ratio	>50db	
PTZ		
Horizontal Rotation Speed	80°/S	
Horizontal Rotation Range	0°~360°	
Tilt Rotation Speed	60°/S	
Tilt Rotation Range	0°~93°	
Preset Points	220	
Guard Tours	3 groups	
Guard Points	Max.16 points	
Lens		
Focus Length	5.35mm-96.3mm	
Focus Control	18X Optical Zoom	
Night Vision		
Infrared LED	∅ 42x6PCS IR LEDS + 2PCS Laser LED	
IR Range	120	
Day-night mode	AUTO	
Network		
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P	
ONVIF	Support	
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA	
Main Stream1	1920*1080@30fps	
Main Stream2	1280*720@30fps	
Sub Stream1	800*448@30fps	
Sub Stream2	704*576@30fps	
Sub Stream3	640*360@30fps	
Sub Stream4	352*288@30fps	
AI Function		
Smart Analytic	3D Human Tracking、 Intrusion Detection、 Line Cross Detection、 Alarm Detection	
Tracking effective range	5~80M Speed: 3~12KM/h	
Interface		
Audio	2-Way Audio	
Alarm	/	
SD Card Slot	/	
POE	Optional	
General		

Weatherproof	IP66
Operating Temperature	-40°~ +70°
Operating Humidity	≤90% Non Condensing
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	25.5 x 21.5 x 41.0 (cm)
Weight	3.1Kgs

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com