



◆ SPECIFICATION

Model	PT5AM22XH500
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H265
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	45°/s
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/s
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
Night Vision	
Infrared LED	∅ 42x6PCS
IR Range	120m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	2560*1920@20fps
Main Stream2	2560*1440@25fps
Main Stream3	2304*1296@25fps
Main Stream4	1920*1080@25fps
Main Stream5	1280*720@25fps
Main Stream6	640*512@25fps
Sub Stream1	800*448@25fps
Sub Stream2	704*576@25fps
Sub Stream3	640*360@25fps
Sub Stream4	352*288@25fps
Interface	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional

General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~+40° Outdoor: -40°~+60°
Operating Humidity	≤90% Non Condensing
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	29.5x28x17(cm)
Weight	4.2Kgs

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com