



◆ SPECIFICATION

Model		PTDK4XH500
Camera		
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	
Horizontal Resolution	5MP	
Compression	H.264/H.265	
S/N Ratio	>50db	
PTZ		
Horizontal Rotation Speed	30°/S	
Horizontal Rotation Range	0°~180°	
Tilt Rotation Speed	25°/S	
Tilt Rotation Range	-45°~40°	
Preset Points	220	
Guard Tours	3 groups	
Guard Points	Max.16 points	
Lens		
Focus Length	2.8mm-12mm	
Focus Control	4X Optical Zoom	
Night Vision		
Infrared LED	35μx6PCS	
IR Range	80m	
Day-night mode	AUTO	
Network		
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P	
ONVIF	Support	
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA	
Main Stream1	2560*1920@20fps	
Main Stream2	2560*1440@25fps	
Main Stream3	2304*1296@25fps	
Main Stream4	1920*1080@25fps	
Main Stream5	1280*720@25fps	
Main Stream6	640*512@25fps	
Sub Stream1	800*448@25fps	
Sub Stream2	704*576@25fps	
Sub Stream3	640*360@25fps	
Sub Stream4	352*288@25fps	
Interface		
Audio	Optional	
Alarm	/	
SD Card Slot	/	
POE	Optional	

General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~+40° Outdoor: -40°~+60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/3A
Lightning Protection	Transient voltage 6000V
Dimension	39.6x19.6x16(cm)
Weight	3Kgs

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com