



◆ SPECIFICATION

Model NO.	KHSD1HTC500FEH	KHSD1HTC500FSH	KHSD1HTC500FK
Video Output Mode	AHD/TVI:5M@20fps/12.5fps,	AHD/TVI:5M@20fps/12.5fps,	AHD/TVI: 5M@20fps/12.5fps,
<b>Camera</b>			
Image Sensor	1/3" CMOS Sensor	1/2.8" SONY Starvis Back-	1/2.5" CMOS sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080	5M:2592*1944 4M:2560*1440 2M:1920*1080	5M:2592*1944 4M:2560*1440 2M:1920*1080
Electronic Shutter	AUTO	AUTO	AUTO
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan
<b>Lens</b>			
Focus Length	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed
<b>Night Vision</b>			
IR Cut Filter	YES	YES	YES
Infrared LED	/	/	/
Infrared Distance	/	/	/
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control
<b>Camera Features</b>			
Starlight	/	/	/
Day/Night	YES	YES	YES
OSD Menu Language	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO
Noise Reduction	DNR	DNR	DNR
WDR	DWDR	DWDR	DWDR
UTC	YES	YES	YES
<b>General</b>			
Housing	PIR Spy Camera	PIR Spy Camera	PIR Spy Camera
Bracket	NO	NO	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,150mA	DC12V±10%,150mA	DC12V±10%,150mA
Dimension	∅ 119 x 56(H) mm	∅ 119 x 56(H) mm	∅ 119 x 56(H) mm
Weight	350g	350g	350g

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICALDEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)