



◆ SPECIFICATION

| Model NO. | KLCBHTC2005XESL | KLCBHTC2005XESP |
|------------------------|--|--|
| Video Output Mode | AHD/TVI/CVI: 2M@30fps/25fps | AHD/TVI/CVI: 2M@30fps/25fps |
| Camera | | |
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor |
| Image Resolution | 2M:1920*1080 | 2M:1920*1080 |
| TV System | PAL/NTSC | PAL/NTSC |
| Electronic Shutter | Auto | Auto |
| Scanning System | Progressive Scan | Progressive Scan |
| Lens | | |
| Focus Length | 2.8-12mm Motor Zoom | 2.8-12mm Motor Zoom |
| Focus Control | Auto | Auto |
| Lens Type | Auto | Auto |
| Night Vision | | |
| IR Cut Filter | YES | |
| Infrared LED | 42μ x 2PCS | |
| Infrared Distance | 30M | |
| IR Status | AGC Auto Control | |
| Camera Features | | |
| Starlight | YES | YES |
| Day/Night | YES | YES |
| OSD Menu | YES | YES |
| WDR | YES | YES |
| UTC | YES | YES |
| Noise Reduction | 3DNR | 3DNR |
| White Balance | AUTO / MANUAL | AUTO / MANUAL |
| Gain Control | AUTO | AUTO |
| General | | |
| Housing | IP67 | |
| Bracket | NO | |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max | |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max | |
| Power Source | DC12V±10%, 500mA | |
| Dimension | ∅115 x 113(H) mm | |
| Weight | 800g | |

Cantok (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantok.com> Email: info@cantok.com